



## Datasheet

# LED TUBE T5 SEMI-AUTONOMOUS+



## GENERAL DATA

Input Voltage	100 - 240 VAC	Storage temperature	-20 °C .. +70 °C
Battery Operation	190 - 240 VDC	Operating & storage humidity	10 - 80 % rH
Operating frequency	50 - 60 Hz	Motion sensor technology	Radar (HF)
Power factor	0.92	Motion transmission power	< 1mW
Peak voltage resistance	300 VACrms	Motion sensor frequency	5.80 GHz
Electronic ballast compatible	No	Motion detection range	10m
Form	T8	Adjustable detection range	Yes
Socket	G5	Communication technology	Bluetooth Mesh
Rotatable Socket	Yes	Communication transmission power	2.5mW
Material	Al / PC / PE	Communication frequency	2.4 GHz
Cooling system	Passive / 235 W/(mK)	Communication range	max. 4 - 10m
Cover	Satin	Active time settings	1s-4h
Colour temperature	3000 - 6000 K	Soft light start	Yes
Colour rendering index	80 - 95	Basic light function	Yes
Colour Consistency (Mac Adam)	3	Basic light settings	0-100% / 1% step
Flicker Metric (Pst LM)	0.03	Daylight control	Yes
Stroboscopic effect metric (SVM)	0.02	Group parameterization	Yes
UGR (4H/8H; 70/50/20) (per/par)	<27.8/ <25	Swarm intelligence	No
System efficiency *	147 lm/W	Remote Access	No
Energy Class	D		
Number of switching cycles	> 500'000		
Service Life (L70B10)	70'000 h		
IP Protection class	IP20		
Protection class	II		
Risk group LED	RG0		
Operating temperature	-20 °C .. +45 °C		



SCAN  
CODE FOR  
PRODUCT  
PAGE

\* Power and luminous flux are subject to initial tolerances of +/- 5%. Unless specified otherwise, they are measured as follows: Colour temperature of 4000K, CRI of <80 and Environmental temperature of 25°C.



## LENGTH DEPENDENT DATA

Nominal Length (N)	55 cm	85 cm	115 cm	145 cm
Power *	9.5 W	14.5 W	17.5 W	22.5 W
Useful luminous flux *	1400 lm	2100 lm	2550 lm	3200 lm
Weight	182 g	252 g	312 g	382 g
EAN	7640185682986	7640185682993	7640185683006	7640185683013

## GRAPHICS

### Drawing Information

N	55 cm	85 cm	115 cm	145 cm
L	550 mm	850 mm	1150 mm	1450 mm
D	28 mm	28 mm	28 mm	28 mm
D1	31 mm	31 mm	31 mm	31 mm
A	70 mm	70 mm	70 mm	70 mm
P	7.5 mm	7.5 mm	7.5 mm	7.5 mm



Measured on a 1.5m Tube/37.5cm Roundlight with 4000K and CRI >80



## CONTACT

LEDCity AG  
 Werdstrasse 21  
 CH-8004 Zurich  
 info@ledcity.io

The products of LEDCity are constantly being further developed. The pictures, drawings and specifications shown here represent the current status at the time of publication of this document and cannot be used as a point of a contract. During the validity of this document we reserve the right to make technical or formal changes to our products.

\* Power and luminous flux are subject to initial tolerances of +/- 5%. Unless specified otherwise, they are measured as follows: Colour temperature of 4000K, CRI of <80 and Environmental temperature of 25°C.