



Datasheet

LED TUBE T5 SEMI-AUTONOMOUS



GENERAL DATA

Input Voltage	100 - 240 VAC	Storage temperature	-20 °C .. +70 °C
Battery Operation	190 - 240 VDC	Operating & storage humidity	10 - 80 % rH
Operating frequency	50 - 60 Hz	Motion sensor technology	Radar (HF)
Power factor	0.92	Motion transmission power	< 1mW
Peak voltage resistance	300 VACrms	Motion sensor frequency	5.80 GHz
Electronic ballast compatible	No	Motion detection range	10m
Form	T8	Adjustable detection range	No
Socket	G5	Communication technology	-
Rotatable Socket	Yes	Communication transmission power	-
Material	Al / PC / PE	Communication frequency	-
Cooling system	Passive / 235 W/(mK)	Communication range	-
Cover	Satin	Active time settings	1s-30min
Colour temperature	3000 - 6000 K	Soft light start	Yes
Colour rendering index	80 - 95	Basic light function	Yes
Colour Consistency (Mac Adam)	3	Basic light settings	0-100% / 10% step
Flicker Metric (Pst LM)	0.03	Daylight control	Yes
Stroboscopic effect metric (SVM)	0.02	Group parameterization	No
UGR (4H/8H; 70/50/20) (per/par)	<27.8/ <25	Swarm intelligence	No
System efficiency *	147 lm/W	Remote Access	No
Energy Class	D		
Number of switching cycles	> 500'000		
Service Life (L70B10)	70'000 h		
IP Protection class	IP20		
Protection class	II		
Risk group LED	RG0		
Operating temperature	-20 °C .. +45 °C		



SCAN
CODE FOR
PRODUCT
PAGE

* Power and luminous flux are subject to initial tolerances of +/- 5%. Unless specified otherwise, they are measured as follows: Colour temperature of 4000K, CRI of <80 and Environmental temperature of 25°C.



LENGTH DEPENDENT DATA

Nominal Length (N)	55 cm	85 cm	115 cm	145 cm
Power *	9.5 W	14.5 W	17.5 W	22.5 W
Useful luminous flux *	1400 lm	2100 lm	2550 lm	3200 lm
Weight	182 g	252 g	312 g	382 g
EPREL ID	1152445	1152446	1152452	1152447
EAN	7640185680210	7640185680234	7640185680265	7640185680302

GRAPHICS

Drawing Information

N	55 cm	85 cm	115 cm	145 cm
L	550 mm	850 mm	1150 mm	1450 mm
D	28 mm	28 mm	28 mm	28 mm
D1	31 mm	31 mm	31 mm	31 mm
A	70 mm	70 mm	70 mm	70 mm
P	7.5 mm	7.5 mm	7.5 mm	7.5 mm



CONTACT

LEDCity AG
 Werdstrasse 21
 CH-8004 Zurich
 info@ledcity.io

The products of LEDCity are constantly being further developed. The pictures, drawings and specifications shown here represent the current status at the time of publication of this document and cannot be used as a point of a contract. During the validity of this document we reserve the right to make technical or formal changes to our products.

* Power and luminous flux are subject to initial tolerances of +/- 5%. Unless specified otherwise, they are measured as follows: Colour temperature of 4000K, CRI of <80 and Environmental temperature of 25°C.